




## 全启式、微启式螺纹安全阀

### A28H 16/25/40 型带手柄弹簧全启式安全阀

工作温度	200
适用介质	水、空气、蒸气

A28H-16




公称通径 Nominal diameter DN(mm)	尺寸 Dimensions (mm)				
	d <sub>0</sub>	Rc	L	L <sub>1</sub>	G
15	10	ZG1/2"	37	62	G3/4"
20	12	ZG3/4"	40	65	G1"
25	15	ZG1"	45	72	G1 1/4"
32	20	ZG1 1/4"	55	85	G1 1/2"
40	25	ZG1 1/2"	67	100	G2"
50	32	ZG2"	76	112	G2 1/2"
65	40	ZG2 1/2"	110	135	G3"
80	50	ZG3"	110	145	G4"

### A21H-16C/25/40 A21W-16/25/40P A24F16/25/40 型微启式安全阀

工作温度	A42H 型 200	A21W 型 200	A21F 型 -40 ~ 80
适用介质	A21H 型适用空气、氨、石油气、水等		A21W 型适用腐蚀性气体或液体 A21F 适用 液化石油气

A21H-16




公称通径 Nominal diameter DN(mm)	尺寸 Dimensions (mm)				
	D <sub>0</sub>	d <sub>0</sub>	L	L <sub>1</sub>	G
15	20	12	35	65	G5/8"
20	25	16	42	76	G3/4"
25	31	20	50	84	G1"
32	ZG1 1/4"	25	55	85	G1 1/4"
40	ZG1 1/2"	32	55	84	G1 1/2"
50	ZG2"	40	67	101	G2"
65	ZG2 1/2"	50	76	120	G2 1/2"
80	ZG3"	65	83	135	G3"

### A27H-16/25/40 A27W-16/25/40P 型弹簧微启式安全阀

工作温度	200
适用介质	A27H-16C/25/40 型适用水、空气、蒸气 A27W-16P/25P/40P 型用于腐蚀介质气体

A27H-16



公称通径 Nominal diameter DN(mm)	尺寸 (mm)				
	d <sub>0</sub>	Rc	L	L <sub>1</sub>	G
15	10	ZG1/2"	40	60	ZG1/2"
20	15	ZG3/4"	45	70	ZG3/4"
25	20	ZG1"	50	80	ZG1"
32	25	ZG1 1/4"	55	85	ZG1 1/4"
40	32	ZG1 1/2"	55	84	ZG1 1/2"
50	40	ZG2"	67	101	ZG2"
65	50	ZG2 1/2"	76	120	ZG2 1/2"
80	65	ZG3"	110	135	ZG3"