



直管道摩擦损失简易表

管径 (mm)	25	40	50	65	80	100	125	150	180	200	250	300	
流 量 (L/S)	1	32.7	3.5	0.8									
	2	13.0	1.4	3.1	0.8	0.4							
	4		55	13	3.2	1.6	0.4						
	6			29	7.1	3.3	0.8	0.23					
	8				13	5.9	1.3	0.4	0.16				
	10				20	9.6	2.1	0.63	0.26	0.11			
			15			21.6	6.8	1.3	0.58	0.27	0.13		
			20				8.6	2.7	1.10	0.50	0.26	0.07	
				25			13	4.1	1.6	0.74	0.37	0.12	
				30			19.4	5.9	2.3	1.05	0.53	0.18	0.07
				40			10.7	4.2	1.90	0.93	0.30	0.12	
				50				6.4	2.90	1.50	0.48	0.19	
					60			9.4	4.30	2.10	0.68	0.27	
					70				5.80	2.90	0.93	0.37	
						80			7.70	3.70	1.20	0.49	
						90			9.60	4.70	1.50	0.61	
							100			6.10	1.90	0.76	
							110			7.20	2.30	0.90	
								120		8.50	2.80	1.10	
								130			3.30	1.30	
									140		3.70	1.50	
									160		4.90	2.00	
										180	0.20	2.40	
										200		3.00	